

STANDING SEAM

DRIP TRAY FLASHING




Cladco Drip Tray Flashings are used only in cladding applications of our Standing Seam Sheets. Designed to aid the flow of water at the foot of your cladding to prevent weather damage, our Drip Tray Flashings will also make the Standing Seam installation process simpler.

COLOUR RANGE


NORDIC NIGHT BLACK	SLATE GREY	TILE RED	SILVER FIR GREEN

FLASHING SPECIFICATIONS			
Length	3m		
Dimensions	100mm x 40mm x 20mm x 10mm		
Thickness	0.7mm		
External Finish	GreenCoat® Pural BT		

TEST CERTIFICATIONS			
Quality	CE Marked (BS EN 14783:2013)		
Fire Rating	Class A1 (BS EN 13501)		










SUSTAINABLE MATERIALS

Cladco Standing Seam Roofing
Sheets are manufactured from SSAB
Steel coated with GreenCoat® Pural
BT. The use of Swedish rapeseed oil,
in place of traditional fossil fuel oils,
promotes sustainable production
methods which reduce our
environmental footprint to provide
you with a high-quality, Al fire-rated
roofing and cladding product.

AFTERCARE

Standing Seam Roof Sheets are low-maintenance and require little in the way of upkeep. We recommend, however, that annual inspection of the Sheeting is carried out, and any debris or dirt build up is removed or cleaned away.











ACCESSORIES

Drip Tray Flashings are installed with a range of our Standing Seam Flashings for a sleek finish.



RESISTANCE

Pural BT coated Sheets are weather, corrosion, scratch and UV resistant.



GUARANTEE

Sheets have a long life span of up to 50 years.

PRODUCT ACCESSORIES



J-RAIL FLASHING



TIN SNIPS



CTI ADHESIVE AND SEALANT



ANNULAR RING NAILS



VENT 3 PRO BREATHABLE MEMBRANE

TOOLS REQUIRED





HANDHELD CIRCULAR SAW



RUBBER MALLET

For a full list of tools required, please refer to our Standing Seam Installation Guide.